

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/031102 A1

(51) International Patent Classification⁷: E06B 3/677

(21) International Application Number:
PCT/CA2004/001673

(22) International Filing Date:
27 September 2004 (27.09.2004)

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data:
0322606.5 26 September 2003 (26.09.2003) GB
0327038.6 20 November 2003 (20.11.2003) GB

(71) Applicant and

(72) Inventor: AMBROSE, David, Howard [CA/CA]; 14940 Weston Road, King City, Ontario L7B 1K4 (CA).


(74) Agent: ASQUITH, Anthony; #28 - 461 Columbia Street West, Waterloo, Ontario N2T 2P5 (CA).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM FOR ALLEVIATING IN-VAULT CONDENSATION IN DOUBLE-GLAZED WINDOWS



(57) Abstract: A hole is drilled through from the outside atmosphere into the between-panes vault, and into the hole is inserted a normally-open valve assembly. The valve is arranged to close responsively to the presence of a pressure differential in such direction that air would tend to enter the vault.

WO 2005/031102 A1